

Figure: 30 TAC §115.453(a)(1)(C)(i)

| <b>Table 1.</b>                                      |  |  |
|--|--|--|
| <b>Coating Category</b>                              | <b>Air-Dried<br/>pounds of volatile<br/>organic<br/>compounds<br/>per gallon coating</b> | <b>Baked<br/>pounds of volatile<br/>organic<br/>compounds<br/>per gallon coating</b> |
| General Coating, One-Component                       | 2.8  | 2.3  |
| General Coating, Multi-Component                     | 2.8  | 2.3  |
| Camouflage Coating                                   | 3.5  | 3.0  |
| Electric-Insulating Varnish Coating                  | 3.5  | 3.0  |
| Etching Filler Coating                               | 3.5  | 3.0  |
| Extreme High-Gloss Coating                           | 3.5  | 3.0  |
| Extreme Performance Coating                          | 3.5  | 3.0  |
| Heat-Resistant Coating                               | 3.5  | 3.0  |
| High Performance Architectural Coating               | 6.2  | 6.2  |
| High Temperature Coating                             | 3.5  | 3.5  |
| Metallic Coating                                     | 3.5  | 3.0  |
| Military Specification Coating                       | 2.8  | 2.3  |
| Mold-Seal Coating                                    | 3.5  | 3.0  |
| Pan-Backing Coating                                  | 3.5  | 3.5  |
| Prefabricated Architectural Coating, Multi-Component | 3.5  | 2.3  |
| Prefabricated Architectural Coating, One-Component   | 3.5  | 2.3  |
| Pretreatment Coating                                 | 3.5  | 3.0  |
| Repair and Touch-Up Coating                          | 3.5  | 3.0  |
| Silicone Release Coating                             | 3.5  | 3.0  |
| Solar-Absorbent Coating                              | 3.5  | 3.0  |

|                                       |     |     |
|---------------------------------------|-----|-----|
| Vacuum-Metalizing Coating             | 3.5 | 3.0 |
| Drum Coating, New, Exterior           | 2.8 | 2.8 |
| Drum Coating, New, Interior           | 3.5 | 3.5 |
| Drum Coating, Reconditioned, Exterior | 3.5 | 3.0 |
| Drum Coating, Reconditioned, Interior | 4.2 | 4.2 |

| <b>Table 2.</b>                                      |   |   |
|--|---|---|
| <b>Coating Category</b>                              | <b>Air-Dried<br/>pounds of volatile<br/>organic<br/>compounds<br/>per gallon solids</b> | <b>Baked<br/>pounds of volatile<br/>organic<br/>compounds<br/>per gallon solids</b> |
| General Coating, One-Component                       | 4.52  | 3.35  |
| General Coating, Multi-Component                     | 4.52  | 3.35  |
| Camouflage Coating                                   | 6.67  | 5.06  |
| Electric-Insulating Varnish Coating                  | 6.67  | 5.06  |
| Etching Filler Coating                               | 6.67  | 5.06  |
| Extreme High-Gloss Coating                           | 6.67  | 5.06  |
| Extreme Performance Coating                          | 6.67  | 5.06  |
| Heat-Resistant Coating                               | 6.67  | 5.06  |
| High Performance Architectural Coating               | 38.0  | 38.0  |
| High Temperature Coating                             | 6.67  | 6.67  |
| Metallic Coating                                     | 6.67  | 5.06  |
| Military Specification Coating                       | 4.52  | 3.35  |
| Mold-Seal Coating                                    | 6.67  | 5.06  |
| Pan-Backing Coating                                  | 6.67  | 6.67  |
| Prefabricated Architectural Coating, Multi-Component | 6.67  | 3.35  |

|  |      |      |
|--|------|------|
| Prefabricated Architectural Coating, One-Component | 6.67 | 3.35 |
| Pretreatment Coating                               | 6.67 | 5.06 |
| Repair and Touch-up Coating                        | 6.67 | 5.06 |
| Silicone Release Coating                           | 6.67 | 5.06 |
| Solar-Absorbent Coating                            | 6.67 | 5.06 |
| Vacuum-Metalizing Coating                          | 6.67 | 5.06 |
| Drum Coating, New, Exterior                        | 4.52 | 4.52 |
| Drum Coating, New, Interior                        | 6.67 | 6.67 |
| Drum Coating, Reconditioned, Exterior              | 6.67 | 5.06 |
| Drum Coating, Reconditioned, Interior              | 9.78 | 9.78 |