

**Figure: 30 TAC §115.453(a)(1)(C)(ii)**

<b><u>Coating Category</u></b>	<b><u>Air-Dried pounds of volatile organic compounds per gallon coating</u></b>	<b><u>Baked pounds of volatile organic compounds per gallon coating</u></b>
<u>General Coating, One Component</u>	<u>2.3</u>	<u>2.3</u>
<u>General Coating, Multi-Component</u>	<u>2.8</u>	<u>2.3</u>
<u>Camouflage Coating</u>	<u>3.5</u>	<u>3.0</u>
<u>Electric-Insulating Varnish Coating</u>	<u>3.5</u>	<u>3.0</u>
<u>Etching Filler Coating</u>	<u>3.5</u>	<u>3.0</u>
<u>Extreme High-Gloss Coating</u>	<u>2.8</u>	<u>3.0</u>
<u>Extreme Performance Coating</u>	<u>3.5</u>	<u>3.0</u>
<u>Heat-Resistant Coating</u>	<u>3.5</u>	<u>3.0</u>
<u>High Performance Architectural Coating</u>	<u>3.5</u>	<u>3.5</u>
<u>High Temperature Coating</u>	<u>3.5</u>	<u>3.5</u>
<u>Metallic Coating</u>	<u>3.5</u>	<u>3.0</u>
<u>Military Specification Coating</u>	<u>2.8</u>	<u>2.3</u>
<u>Mold-Seal Coating</u>	<u>3.5</u>	<u>3.0</u>
<u>Pan-Backing Coating</u>	<u>3.5</u>	<u>3.5</u>
<u>Prefabricated Architectural Coating, Multi-Component</u>	<u>2.8</u>	<u>2.3</u>
<u>Prefabricated Architectural Coating, One-Component</u>	<u>2.3</u>	<u>2.3</u>
<u>Pretreatment Coating</u>	<u>3.5</u>	<u>3.0</u>
<u>Repair and Touch-Up Coating</u>	<u>3.5</u>	<u>3.0</u>
<u>Silicone Release Coating</u>	<u>3.5</u>	<u>3.0</u>
<u>Solar-Absorbent Coating</u>	<u>3.5</u>	<u>3.0</u>
<u>Vacuum-Metalizing Coating</u>	<u>3.5</u>	<u>3.0</u>
<u>Drum Coating, New, Exterior</u>	<u>2.8</u>	<u>2.8</u>
<u>Drum Coating, New, Interior</u>	<u>3.5</u>	<u>3.5</u>
<u>Drum Coating, Reconditioned, Exterior</u>	<u>3.5</u>	<u>3.0</u>
<u>Drum Coating, Reconditioned, Interior</u>	<u>4.2</u>	<u>4.2</u>