

**Figure: 30 TAC §115.453(a)(5)**

**[Figure: 30 TAC §115.453(a)(5)]**

Table 1.

<u>Coating Category</u>	<u>Limit Grams of VOC per liter coating, less water and less exempt compounds</u>
<u>Bond Breakers</u>	<u>350</u>
<u>Building Envelope Coatings</u>	<u>50</u>
<u>Concrete-Curing Compounds</u>	
<u>Concrete-Curing Compounds for Roadways and Bridges</u>	<u>350</u>
<u>Concrete-Curing Compounds, Other than for Roadways and Bridges</u>	<u>100</u>
<u>Concrete Surface Retarder</u>	<u>50</u>
<u>Default Coatings</u>	<u>50</u>
<u>Driveway Sealer</u>	<u>50</u>
<u>Dry-Fog Coatings</u>	<u>50</u>
<u>Faux Finishing Coatings</u>	
<u>Clear Topcoat</u>	<u>100</u>
<u>Decorative Coatings</u>	<u>350</u>
<u>Glazes</u>	<u>350</u>
<u>Japans</u>	<u>350</u>
<u>Trowel Applied Coatings</u>	<u>50</u>
<u>Fire-Resistive Coatings</u>	<u>150</u>
<u>Flat Coatings</u>	<u>50</u>
<u>Floor Coatings</u>	<u>50</u>
<u>Form Release Compound</u>	<u>100</u>
<u>Graphic Arts (Sign) Coatings</u>	<u>200</u>
<u>Magnesite Cement Coatings</u>	<u>450</u>
<u>Mastic Coatings</u>	<u>100</u>
<u>Metallic Pigmented Coatings</u>	<u>150</u>
<u>Multi-Color Coatings</u>	<u>250</u>

<u>Nonflat Coatings</u>	<u>50</u>
<u>Pre-Treatment Wash Primers</u>	<u>420</u>
<u>Primers, Sealers, and Undercoaters</u>	<u>100</u>
<u>Reactive Penetrating Sealers</u>	<u>350</u>
<u>Recycled Coatings</u>	<u>150</u>
<u>Roof Coatings</u>	
<u>Roof Coatings, Other than Aluminum</u>	<u>50</u>
<u>Roof Coatings, Aluminum</u>	<u>100</u>
<u>Roof Primers, Bituminous</u>	<u>350</u>
<u>Rust Preventative Coatings</u>	<u>100</u>
<u>Sacrificial Anti-Graffiti Coatings</u>	<u>50</u>
<u>Shellacs</u>	
<u>Clear</u>	<u>730</u>
<u>Pigmented</u>	<u>550</u>
<u>Specialty Primers</u>	<u>100</u>
<u>Stains</u>	
<u>Stains, Other than Interior</u>	<u>100</u>
<u>Stains, Interior</u>	<u>250</u>
<u>Stone Consolidants</u>	<u>450</u>
<u>Swimming Pool Coatings</u>	
<u>Repair</u>	<u>340</u>
<u>Other</u>	<u>340</u>
<u>Tile and Stone Sealers</u>	<u>100</u>
<u>Tub and Tile Refinishing Coatings</u>	<u>420</u>
<u>Waterproofing Sealers</u>	<u>100</u>
<u>Waterproofing Concrete/Masonry Sealers</u>	<u>100</u>
<u>Wood Coatings</u>	
<u>Varnish</u>	<u>275</u>
<u>Sanding Sealers</u>	<u>275</u>
<u>Lacquer</u>	<u>275</u>
<u>Other</u>	<u>275</u>
<u>Wood Conditioners</u>	<u>100</u>
<u>Wood Preservatives</u>	
<u>Below-Ground</u>	<u>350</u>
<u>Other</u>	<u>350</u>

Table 2.

<u>Coating Category</u>	<u>Limit</u> <u>Grams of VOC Per Liter of Material</u>
<u>Low-Solids Coating</u>	<u>120</u>

Table 3.

<u>Coating Category</u>	<u>Limit</u> <u>Grams of VOC Per Liter of Colorant</u> <u>Less Water and Less Exempt</u> <u>Compounds</u>
<u>Colorant added to Architectural Coatings,</u> <u>excluding IM Coatings</u>	<u>50</u>