

**Figure: 30 TAC §115.463(f)**

<u>Solvent Cleaning Category</u>	<u>VOC Content Limit (pounds VOC per gallon)</u>	<u>VOC Content Limit (grams VOC per liter)</u>
<u>(A) Product Cleaning During Manufacturing Process or Surface Preparations for Coating, Adhesives, or Ink Application</u>		
<u>(i) General</u>	<u>0.21</u>	<u>25</u>
<u>(ii) Electrical Components and Electronic Components</u>	<u>0.83</u>	<u>100</u>
<u>(iii) Medical Devices and Pharmaceuticals</u>	<u>6.7</u>	<u>800</u>
<u>(B) Repair and Maintenance Cleaning</u>		
<u>(i) General</u>	<u>0.21</u>	<u>25</u>
<u>(ii) Electrical and Electronic Components</u>	<u>0.83</u>	<u>100</u>
<u>(iii) Medical Devices and Pharmaceuticals</u>		
<u>(A) Tools, Equipment, Machinery</u>	<u>6.7</u>	<u>800</u>
<u>(B) Medical or Pharmaceutical Work Surfaces</u>	<u>5.0</u>	<u>600</u>
<u>(C) Cleaning of Coatings or Adhesives Application Equipment</u>	<u>0.21</u>	<u>25</u>
<u>(D) Cleaning of Ink Application Equipment</u>		
<u>(i) General</u>	<u>0.21</u>	<u>25</u>
<u>(ii) Flexographic Printing</u>	<u>0.21</u>	<u>25</u>
<u>(iii) Gravure Printing</u>		
<u>(A) Publications</u>	<u>0.83</u>	<u>100</u>
<u>(B) Packaging</u>	<u>0.21</u>	<u>25</u>
<u>(iv) Lithographic (Offset) or Letter Press Printing</u>		
<u>(A) Roller Wash, Blanket Wash, and On-press Components</u>	<u>0.83</u>	<u>100</u>
<u>(B) Removable Press Components</u>	<u>0.21</u>	<u>25</u>
<u>(v) Screen Printing</u>	<u>0.83</u>	<u>100</u>

<u>Solvent Cleaning Category</u>	<u>VOC Content Limit (pounds VOC per gallon)</u>	<u>VOC Content Limit (grams VOC per liter)</u>
<u>(vi) Ultraviolet Ink/Electron Beam Ink Application Equipment (except screen printing)</u>	<u>0.83</u>	<u>100</u>
<u>(vii) Specialty Flexographic Printing</u>	<u>0.83</u>	<u>100</u>
<u>(E) Cleaning of Polyester Resin Application Equipment</u>	<u>0.21</u>	<u>25</u>